



Sede operativa/Operation and delivery to:

UR FOG S.R.L. - Via Toscana 38 - 10099 San San Mauro T.se (TO)

Sede legale/Legal Office: Via Giacinto Collegno 11 - 10143 Torino (TO)

Tel: +39011/0133037 Fax: 011/0133005

E-mail: sales1@urfog.com Internet: www.urfog.com

C.F./P.IVA IT10724850010 - Reg. Imprese TO - 1157030 Cap.Soc. Euro 11.000,00 i.v

Numero Iscrizione Registro AEE: IT19050000011412

Numero Iscrizione Registro Pile: IT19100P00005758

Contributo CONAI assolto ove dovuto

Rev.-3 June 2020

Technical Datasheet

PURIFOG HYPO

MIXTURE

Description

The new Purifog Hypo mixture, sprayed exclusively through UR FOG thermospray systems, cleans and hygienizes air and surfaces. Thanks to a greater concentration of active elements and the presence of sodium hypochlorate, it is able to perform an even more aggressive and lasting action.

Specifications

Appearance:	Liquid
pH:	7,0 ± 1,0
Odour:	Characteristic
Solubility:	Complete

Content (Reg. CE 648/2004)

non-ionic surfactants >5% - <15%, non-ionic surfactants <5%, sodium hypochlorite, perfumes. It contains limonene, geraniol, linalool, citral, linalyl acetate

Labelling



DANGER

Causes severe skin burns and eye damage.
Very toxic to aquatic life.
Toxic to aquatic life with long lasting effects.

Precautionary statements:

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash hands Thoroughly after handling.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or a doctor.

Wash contaminated clothing before reuse.

Collect spillage.

Store locked up.

Dispose of contents/container in accordance with applicable regulations.

Warning: Do not open the box. Use Purifog only for spraying. Spray only through UR FOG thermospray systems. In case of contact with eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of skin contact wash with plenty of water and soap. In case of ingestion do not induce vomiting under any circumstances. ASK FOR A MEDICAL EXAMINATION IMMEDIATELY.

Instructions for use

- Preparation for use:

PURIFOG HYPO is a special mixture to be sprayed exclusively through URFog Fogging Systems.

This fluid must be sprayed indoors in the absence of people and/or animals. The mixture, once sprayed, generates a thick fog that persists for a few hours inside the room during which the entrance to the room is absolutely forbidden.

For installation and configuration, follow the "Installation and Use Manual" contained in the URFog Fogging System package.

The amount of fog to be dispensed, i.e. the shooting time, can be set in seconds.



Sede operativa/Operation and delivery to:

UR FOG S.R.L. - Via Toscana 38 - 10099 San San Mauro T.se (TO)

Sede legale/Legal Office: Via Giacinto Collegno 11 - 10143 Torino (TO)

Tel: +39011/0133037 Fax: 011/0133005

E-mail: sales1@urfog.com Internet: www.urfog.com

C.F./P.IVA IT10724850010 - Reg. Imprese TO - 1157030 Cap.Soc. Euro 11.000,00 i.v

Numero Iscrizione Registro AEE: IT19050000011412

Numero Iscrizione Registro Pile: IT19100P00005758

Contributo CONAI assolto ove dovuto

Rev.-3 June 2020

Technical Datasheet

PURIFOG HYPO

MIXTURE

To set the shooting time, which varies depending on the size of the environment to be treated, see the section "Shooting Time Settings" in the "Installation and Use Manual" contained in the URFog Fogging System package.

In order to achieve a complete and deep hygienization of the environment it is recommended to set an increased the shooting time by 50% compared to what is indicated in the manual.

For the replacement of the PURIFOG HYPO bag, follow the section "Installation, replacement and reset bag" within the "Installation and Use Manual" contained in the package of the URFog Fogging System.

- Instructions for use:

Step 1: Once the preliminary steps described above have been completed, start spraying the PURIFOG HYPO mixture

Step 2: At the end of each spray cycle it is necessary to eliminate the residue of the PURIFOG HYPO solution inside the boiler of the fogging system. To start this procedure, simply replace the PURIFOG HYPO bag with a bag containing the CLEAN-NLS solution and start a 10-second spraying (20 seconds for Pump Pro Plus 1500 and 4000 models). In case the fogging system is used several times a day to spray the PURIFOG HYPO mixture, proceed with step 2 after the last spraying.

During the dispensing and in the next 8 hours, people and/or animals are prohibited from entering the premises.

About 8 hours after the spraying has taken place, all the fog will be completely deposited and, after careful ventilation of the room, it will be possible to stay inside.

On the surfaces will remain a very light layer imperceptible as additional protection of surfaces.

For effective cleaning/hygenizing action, pass, after spraying, a damp cloth on the surfaces with which PURIFOG HYPO came into contact. Rinse the surface if it needs to come into direct contact with food. In the presence of delicate fabrics and/or surfaces, check the product's compatibility in advance.

Attach to the business plan datasheet and safety factsheet for employment in professional activities subject to the application of D.Lgs. 193/07 (H.A.C.C.P.) and D.Lgs. 81/08 and s.m